



EN	D	E	F	I
Cable duct rodding system GIRAVOLTA TWIST with polyester (PET) <i>helical</i> rod ø 3,5 mm complete with starting/ending M4 threaded junctions and accessories.	Kabeleinziehgerät GIRAVOLTA TWIST mit <i>verdrittem</i> Polyesterband (PET) ø 3,5 mm, komplett mit Anfangs/Endhülse M4 und Zubehör.	Sistema pasa cables GIRAVOLTA TWIST con <i>guía espiral</i> en poliestere (PET) ø 3,5 mm, con casquillo roscado M4 y accesorios.	Appareils tirefils GIRAVOLTA TWIST avec sonde <i>torsade</i> en Polyester (PET) ø 3,5 mm, avec douilles filetées d'extrémité M4 et accessoires.	Sonda passacavi GIRAVOLTA TWIST con sonda <i>spirata</i> in poliestere (PET) ø 3,5 mm, completa di raccordi iniziali/finali M4 e accessori.
Packaging: Single box 277 x 263 x 103 mm	Verpackt: im Einzelkarton 277 x 263 x 103 mm	Embalaje: caja de cartón individual 277 x 263 x 103 mm	Emballage: Boîte en carton 277 x 263 x 103 mm	Imballo: cartone singolo 277 x 263 x 103 mm

art.	ø mm	m	kg	rod colours	case colours	dimensions mm
GVGTS320V	3,0	20	1,40	RAL 6038	black/green	
GVGTS330V		30	1,50			
GVGTS320G	3,5	20	1,40	RAL 1026	blue/yellow	
GVGTS330G		30	1,50			

ø 3,0 mm	ø 8-32 mm	+++	120 mm	400 kg	110 kg	20-30 (+ 2÷3) m
ø 3,5 mm	ø 8-32 mm	++	80 mm	400 kg	110 kg	20-30 (+ 2÷3) m

Subject to technical changes without prior notice. Technische Änderungen vorbehalten. Sujeto a variaciones técnicas sin previo aviso. Sujet à des modifications techniques sans préavis. Soggetto a variazioni tecniche senza preavviso.