



EN Flat steel rod **VOLTASTEEL FLAT COVERED ø 10 mm**, covered with PP, with **interchangeable** terminals, complete of flexible starting spinner with eyelet and starting spinner with eyelet.

D Flachstahl Band **VOLTASTEEL FLAT COVERED ø 10 mm**, mit PP-Ummantelung, mit **austauschbaren Endstücken**; Federführungskopf mit Öse und Zugkopf mit Öse.

E Pasacables **VOLTASTEEL FLAT COVERED ø 10 mm**, de hilo plano de acero recubierto de PP, con cabeza guía flexible y anilla de enganche, terminales **intercambiables**.

F Tire-fils **VOLTASTEEL FLAT COVERED ø 10 mm**, en acier avec gaine en PP, avec des terminaux, tête flexible et embout **interchangeables**.

I Sonda passacavi **VOLTASTEEL FLAT COVERED ø 10 mm**, in piatto armonico rivestito in PP, con terminali fissi **intercambiabili**, completa di testa flessibile con asola e ogiva iniziale con asola.

art.	ø mm		RAL	m	kg
GVAPR10RIC40	10	 8 x 2 mm	5015	40	7,30
GVAPR10RIC50				50	9,10
GVAPR10RIC60				60	10,80
GVAPR10RIC70				70	12,70
GVAPR10RIC80				80	14,40
GVAPR10RIC90				90	16,40
GVAPR10RIC100				100	18,00
GVAPR10RIC120				120	21,60

ø 10,0 mm	ø 63-150 mm	++	800 mm	1900 kg	800 kg	40-120 (+ 3÷5) m

Subject to technical changes without prior notice. Technische Änderungen vorbehalten. Sujeto a variaciones técnicas sin previo aviso. Sujet à des modifications techniques sans préavis. Soggetto a variazioni tecniche senza preavviso.